

3MP TP Pan-Tilt Camera With 4G-SIM



FEATURES

- 3MP pan/tilt Smart Mini PT 4G Camera
- Horizontal rotation of 350 degrees, vertical rotation of 90 degrees
- Built-in high-sensitivity MIC and speaker, support two-way audio
- With white light and infrared light, support Two night vision mode : B/W mode, full color mode
- Support human detection. The device can turn on white light when someone into the monitoring area. And the real-time alarm push information is sent on mobile app
- Motion Tracking. When a human figure is detected will be track Automatically • Built-in Siren. Siren will be trigger when human movement is detected. The voice of
- the siren can be customized.
- Built-in PIR Sensor

Support

- Built-In Battery 10400mAh Rechargeable lithium battery, With 7W Solar Panel
- Unique With All-Time-Color vision
- Support Micro SD Card Up to 256GB & Cloud Storage (Optional)
- 4G Essecloud, scan the QR code to easily connect the camera
- Support monitoring : PC/Mobile on Essecloud
- IP66 Waterproof Rating, 4000 Lightning Protection
- Compression : H.264 / H.265 / H.265+



Resolution SD Card

Battery Backup



-----Location

Presets

Cloud Recording

Technical Specifications

Product Code

Image Sensor Resolution Video Compression Standard Lens

Infrared LED Infrared IR Distance White LED White IR Distance Light Mode Minimum Illumination Video Encode Stream PTZ Rotation Range Audio Input / Output Audio Compression Standard WDR **Electronics Shutter** 4G Frequency Band **PIR Detection** Alarm

UV-4GPT-DA30T2-CA
1/2.8" CMOS Sensor
3MP:2560 x 1440
H.264+ / H.265 / H.265+
4mm @ F2.0, View angle: Horizontal 88.9° , Vertical 47.5°,
106.3° Diagonal
4 LED
30 Meters
4 LED
30 Meters
Full color / Infrared
Color : 0.01Lux, Black and White : 0.001 Lux
Main stream : 2304x1296 / 15FPS; Substream: 640x360 / 15FPS
Horizontal 350° 0.1°~20°/sec, Vertical 105° 0.1°-20°/sec;
Supports two-way audio, built-in microphone and speaker
AAC / G711A
Support DWDR
Auto
FDD-LTE : B1/ B3/ B5/ B8; TDD-LTE : B34/ B38/ B39/ B40/ B41;
8-10 Meter
1) Motion Detection, Alarm Picture Push
2) Human Detection
Android & iPhone / Windows PC (Application Truecloud)

Monitoring

Storage	Support Micro SD card (Max 256G)
Solar Panel	7W
Power Supply	Built-In Rechargeable 18000mAh Battery
Power Input	Type-C DC 5V-2A
Working Temp	0~50℃ RH Less than 95% (No condensation)
Storage Temperature/Humidity	-20°C to +60°C / 20% to 90% RH
Housing Type	Plastic [IP66]
Dimension	132 x 191 x 170mm (WxHxL)
Net Weight	0.723kg
Gross Weight	0.978kg

Similar Products



4G 3MP Solar With Battery Bullet Camera



Smart 4G 3MP Dual Lens Linkage PT Camera



Solar Panel 12Ah



4G 3MP Mini PT Camera



4G 3MP Dual Lens Mini PT Camera



4G 3MP PTZ Camera

* Note: Product specifications are subject to change without prior notice.